

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 493 525 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
05.01.2005 Bulletin 2005/01

(51) Int Cl.7: **B23K 9/32, B23K 9/173**

(21) Application number: **04012055.2**

(22) Date of filing: **21.05.2004**

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IT LI LU MC NL PL PT RO SE SI SK TR**
Designated Extension States:
AL HR LT LV MK

• Stanzel, Ken
Appleton Wisconsin 54915 (US)
• Vogel, Bernard J
Troy Ohio 45373 (US)

(30) Priority: **02.07.2003 US 604237**

(71) Applicant: **ILLINOIS TOOL WORKS INC.**
Glenview, Cook County, Illinois 60025 (US)

(74) Representative: **Vetter, Ewald Otto et al**
Melssner, Bolte & Partner
Anwaltssozietät GbR
Postfach 10 26 05
86016 Augsburg (DE)

(72) Inventors:
• **Albrecht, Bruce**
Hortonville, Wisconsin 54944 (US)

(54) **Welder with integrated gas bottle**

(57) A welder having an integrated gas cylinder is disclosed. The welder has a power source constructed to condition and output an electrical signal suitable to welding and a gas cylinder disposed in an enclosure.




FIG. 1

EP 1 493 525 A1

Description

BACKGROUND OF THE INVENTION

[0001] The present invention relates generally to welding systems and, more particularly, to a welder having an integrated gas cylinder.

[0002] Welder power sources have become increasingly portable in recent years. This portability is largely the result of lighter unit weight and improved electrical components. One advancement in the area of electrical components has been the incorporation of inverter-type power sources. The application of an inverter power source has reduced the size and weight of welders and created usable space within the confines of the housing, while maintaining the ability to generate the outputs required for welding. Similarly, advances in battery technology allow the incorporation of an energy storage device in a welder to allow easy transport.

[0003] Improvements in wire feeder technology have also improved the ease of use and portability of a welder. Wire welding is generally believed to be easier to learn than conventional stick welding and as such, relatively inexperienced artisans can produce adequate results in relatively little time. As a result, due to the ease of use and versatility of application, many users prefer wire welding over conventional stick welding.

[0004] Space in any work environment is always at a premium. Whether the welder is used in the hobbyist's garage or the machine shop of an industrial plant, the size of the unit is always a design consideration. The space used by a welder is not limited to the dimensions of the power source itself but includes the ancillaries related to welding processes such as cables, consumables, and gas cylinders. The space required for the storage and maintenance of these items is another consideration associated with many welders.

[0005] Shielding gas cylinders provide gas to the welding process. This gas essentially encapsulates the welding process in order to protect the integrity of the weld from contaminants and also enhances arc performance during a welding process. The shielding gas is generally provided in very large and very heavy cylinders. The cylinders are constructed ruggedly to withstand the high pressure of the gas contained therein and the rigors of the workplace. A regulator is typically attached to the gas cylinder and allows the operator of the welding power source to control the amount of gas supplied to the welding process.

[0006] The size and weight of the gas cylinders significantly detracts from the portability of the welder. Additionally, attempts to move the welder and gas cylinder together presents an opportunity for inadvertent damage to the gas cylinder or to the regulator attached thereto unless a large cart is provided. Such carts however are large and typically constructed to accommodate large gas cylinders. Such construction generally results in a large and cumbersome device that is still difficult to

maneuver in confined quarters.

[0007] It would therefore be desirable to design a system and method capable of generating the power necessary for welding having a housing that incorporated a gas cylinder and/or regulator all enclosed within the housing of the welder.

BRIEF DESCRIPTION OF THE INVENTION

[0008] The present invention is directed to a welding system that solves the aforementioned drawbacks. The present invention provides a system and method for a welder that is portable and includes a shielding gas cylinder therein.

[0009] Therefore in accordance with one aspect of the present invention, a welding-type apparatus is disclosed having a power source constructed to condition and output an electrical signal suitable to welding located in an enclosure. A gas cylinder is disposed within the enclosure and provides shielding gas for welding. As such, the enclosure completely encloses the gas cylinder thereby providing convenient storage for the gas cylinder and regulator.

[0010] In accordance with another aspect of the present invention, a welder is disclosed having a power source configured to generate welding-type power and deliver the power to a welding gun that is in electrical communication therewith. A gas cylinder is disposed within the power source and connected thereto so that the cylinder supplies gas to the welding gun and is enclosed by the housing of the welder.

[0011] In accordance with a further aspect of the present invention, a method of constructing a welding-type apparatus is disclosed that includes positioning a power source with respect to a base of the apparatus, providing a restraining system to hold a gas cylinder relative to the power source, and forming a housing to enclose both the power source and the restraining system. As such, both the power source and the restraining system are enclosed by the housing.

[0012] In accordance with yet another aspect of the present invention, a welder-type device is presented having a housing with an opening to allow passage of a gas cylinder therethrough. The welder-type device has a means for supplying welding power and a means for retaining a gas cylinder within the housing. Therefore, a gas cylinder positioned within the housing can be securely fastened thereto.

[0013] Therefore, the present invention provides a welder power source with a gas cylinder housed therein. Such a construction allows for a welder power source that is lightweight and transportable with a gas cylinder securely housed therein.

[0014] Various other features, objects and advantages of the present invention will be made apparent from the following detailed description and the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0015] The drawings illustrate one preferred embodiment presently contemplated for carrying out the invention.

[0016] In the drawings:

Fig. 1 is a front-side perspective view of a welder according to the present invention.

Fig. 2 is a rear-side perspective view of the welder of Fig. 1 having an alternate housing attached thereto.

Fig. 3 is a perspective view of the power source of Fig. 1 with the cover removed.

Fig. 4 is a perspective rear-side view of the power source of Fig. 2 with the cover removed.

Fig. 5 is a perspective view of the cover of an opening for the gas cylinder of the power source of Figs. 2 and 4.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0017] As one skilled in the art will fully appreciate the hereinafter description of welding devices not only includes welders but may also include any system that requires high power outputs, such as heating and cutting systems that require gas cylinders. Therefore, the present invention is equivalently applicable with any device requiring high power output in conjunction with a gas cylinder system, including welders, plasma cutters, heaters, and the like. Reference to welding power, welding-type power, or welders generally, includes welding, cutting, or heating power. Description of a welding apparatus illustrates just one embodiment in which the present invention may be implemented. Understandably, the present invention is equivalently applicable with other systems, such as for cutting and heating.

[0018] Referring now to Fig. 1, a perspective view of a welding device incorporating the present invention is shown. Welding device 10 includes a housing 12 enclosing the internal components of the welding device under a cover 14. Optionally, the welding device 10 includes a handle 16 for transporting the welding system from one location to another. To effectuate the welding process, such as TIG or MIG welding, the welding device includes a torch 18 as well as a work clamp 20. The work clamp 20 is configured to ground a workpiece 22 to be welded. As is known, when the torch 18 is in relative proximity to workpiece 22, a welding arc or cutting arc results, depending upon the particular welding desired. A pair of cables 24 and 26 connects the torch 18 and work clamp 20 to the housing 12, respectively.

[0019] As shown in Fig. 1, cover 14 has a door 28 located therein which allows access to an interior of welding device 10. Door 28 covers an opening 30 in housing 12 and has a hinge 32 connecting door 28 thereto. Opening 30 is configured to allow for the passage of a

gas cylinder 34 (shown in phantom under cover 14) therethrough. Hinge 32 of door 28 allows door 28 to be pivotally opened and closed over opening 30. The hinge may also be placed on a bottom side 36 of the door 28.

5 [0020] Fig. 2 shows an alternate embodiment of the opening for the gas cylinder 34. Preferably, a cover 38 is threadingly engaged to a rear panel 40 of housing 12. Cover 38 is removable to allow for placement of a gas cylinder 34 into a gas cylinder chamber 42. Cover 38 can be constructed to retain a base 44 of the gas cylinder 34. In this manner, a support 46 is provided at a front end 48 of gas cylinder chamber 40 and gas cylinder 34 is effectively retained between support 46 and cover 38. Although shown as positioned in a rear or a side panel of the housing, such openings are only by way of example and do not limit the scope of the claims presented herein.

[0021] Fig. 3 shows a detailed view of the embodiment of Fig. 1 with cover 38 moved to expose an interior 50 of welding device 10. A wire feeder 52 is disposed in interior 50 of welding device 10 and in electrical communication with a power source 54, also located therein and attached to a base 56 of housing 12. Wire feeder 52 provides a consumable material, such as wire 58, to torch 18 during the welding process. Shielding gas is also provided to torch 18 during the welding process from gas cylinder 34.

[0022] Gas cylinder 34 is located within housing 12 of welding device 10 and held in place by a means for retaining the gas cylinder, in this embodiment, a restraint 60. Restraint 60 maintains the position of gas cylinder 34 relative to power source 54. A body 62 extends from base 44 of gas cylinder 34 to an outlet end 64. Outlet end 64 of gas cylinder 34 is constructed to engage a first adapter 66 of a regulator 68. The means for retaining 60 can be of many different configurations such as that shown with reference to Figs. 4 and 5, as will be discussed below, or, as that shown in Fig. 3, a pair of straps 70, 72 that hold body 62 of gas cylinder 34 and prevents movement of gas cylinder 34 relative to power source 54. Such a construction prevents the inadvertent disengagement of gas cylinder 34 from first adapter 66 of regulator 68.

[0023] The second embodiment of the means for retaining is shown in Fig. 4. Cover 38, also shown in Fig. 5, extends into interior 50 of welding device 10 extending past rear panel 40. Cover 38 is constructed to engage base 44 of gas cylinder 34 and thereby create a compressive force 74 between support 46 and rear panel 40 of housing 12 with gas cylinder 34 disposed therebetween. The construction of support 46 and cover 38 secure gas cylinder 34 relative to power source 54 within housing 12 of welder 10. Regardless of which embodiment is applied, gas cylinder 34 is located within a perimeter of housing 12 and held securely therein.

[0024] Also shown in Figs. 3 and 4, first adapter 66 of regulator 68 is constructed to engage outlet end 64 of gas cylinder 34 inside housing 12 and still allow user

control over the function of the regulator. A dial 86 and/or a pressure gauge 88 extend from regulator 68 through a front panel 90 of housing 12. Dial 86 and/or pressure gauge 88 allow a user to adjust and determine a delivery pressure of shielding gas to torch 18 from gas cylinder 34. Dial 86 and pressure gauge 88 are positioned in a control area 92 of front panel 90 so that a majority of the controls of the welding device are adjustable from a control area 92 of device 10. In addition to first adapter 66 of regulator 68, regulator 68 also has a second adapter 94, which is discussed below.

[0025] As shown in Figs. 4 and 5, cover 38 has a threaded section 76 that engages a threaded opening 78 in rear panel 40. Threaded opening 78 is sized to accommodate the passage of gas cylinder 34 therethrough. An inner surface 80 of cover 38 is constructed to engage base 44 of gas cylinder 34 and includes a pad 81 attached thereto. A plurality of protrusions 82 extend from an outer surface 84 of cover 38 and allows a user to turn cover 38 into threaded engagement with rear panel 40 without additional tools. It is understood that protrusion 82 could be any shape desired, or even a recess into cover 38, and constructed to engage a driving tool.

[0026] Second adapter 94 extends from regulator 68 through rear panel 40 and is constructed to engage a bulk cylinder 96. Bulk cylinder 96 also has a regulator 98 attached thereto. A connection means 100 extends from regulator 98 to second adapter 94 of welding device 10. As such, regulator 68, which is, in part, located in control area 92 of front panel 90 is constructed to control the flow of shielding gas from either gas cylinder 34 and/or bulk cylinder 96. This construction provides for the connection of a second gas cylinder to the welding device when desired, such as when the welder is located at a primary operating position such as a shop or a garage. Additionally, this construction provides that the gas cylinder located within the welding device is reserved for remote operations away from the bulk tank. The construction also prevents excessive changing of gas cylinders when a bulk cylinder is available. Additionally, the user is not required to transport a heavy and awkward bulk cylinder but can simply disconnect the bulk cylinder at second adapter 94 and move the welder to a desired position with gas cylinder 34 located securely within housing 12.

[0027] The present invention is also equally applicable with a built-in plasma cutting system. Such a system may have a built-in supply of compressed air, or may be equipped to receive compressed air from an external source. The built-in supply of compressed air may be a bottle or a compressor. The invention can be used in any welding-type apparatus, and is especially applicable for TIG and/or MIG welding processes. It is also noted that the gas cylinder may contain inert or active gases. Such gases can include, but are not limited to, argon, CO₂, oxygen, compressed air, or another suitable gas/mixture suitable for such uses. In general then, the in-

vention is applicable to any of the aforementioned welding-type applications that would benefit from the use of gas bottle.

[0028] Therefore, in accordance with one embodiment of the present invention, a welding-type apparatus has a power source constructed to condition and output an electrical signal suitable to welding located in an enclosure. The power source is preferably a light-weight inverter-type power source, an energy storage device, such as a battery, or a combination of the two. The configuration is constructed for ease of transport. In either case, the power source is constructed to produce a welding signal preferably from a 110-120V input, but other inputs are contemplated as well. Such inputs include at least sources ranging from 110V to 575V applications. A gas cylinder is disposed within the enclosure and provides shielding gas to a weld.

[0029] In accordance with another embodiment of the present invention, a welder has a power source configured to generate welding-type power and deliver the power to a welding gun in electrical communication therewith. A gas cylinder is disposed within the power source and connected thereto so that the cylinder supplies gas to the welding gun.

[0030] In accordance with a further embodiment of the present invention, a method of constructing a welding-type apparatus is disclosed that includes positioning a power source within the apparatus, providing a restraining system to hold a gas cylinder relative to the power source, and forming a housing to enclose both the power source and the restraining system.

[0031] In accordance with yet another embodiment of the present invention, a welder-type device has a housing with an opening to allow passage of a gas cylinder therethrough. The welder-type device has a means for supplying welding power and a means for retaining a gas cylinder within the housing.

[0032] The present invention has been described in terms of the preferred embodiment, and it is recognized that equivalents, alternatives, and modifications, aside from those expressly stated, are possible and within the scope of the appending claims.

Claims

1. A welding-type apparatus comprising:

an enclosure;
a power source constructed to condition and output an electrical signal suitable to welding and located in the enclosure; and
a gas cylinder disposed within the enclosure.

2. The welding-type apparatus of claim 1 wherein the power source is at least one of an inverter, an energy storage device, and a combination of an inverter and an energy storage device constructed to out-

put an electrical signal capable of welding.



3. The welding-type apparatus of claim 1 or 2 further comprising a wire feeder constructed to feed a consumable wire to a welding gun and wherein the gas cylinder is constructed to provide a shielding gas. 5
4. The welding-type apparatus of claim 3 wherein the wire feeder is disposed within the enclosure. 10
5. The welding-type apparatus of at least one of the preceding claims further comprising a regulator attached to the gas cylinder and disposed within the enclosure. 15
6. The welding-type apparatus of claim 5 wherein the regulator has a valve and a gauge, wherein each is accessible to a user.
7. The welding-type apparatus of at least one of the preceding claims further comprising a torch constructed to receive gas from the gas cylinder. 20
8. The welding-type apparatus of at least one of the preceding claims wherein the enclosure further comprises an opening in the enclosure to provide passage of the gas cylinder therethrough and a door to close the opening. 25
9. The welding-type apparatus of at least one of the preceding claims further comprising a restraining system to hold the gas cylinder in place for transport. 30
10. The welding-type apparatus of at least one of the preceding claims wherein the gas cylinder is either one of a re-fillable bottle and a disposable bottle. 35



40

45

50

55







European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 04 01 2055

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (InCL.7)
X	DE 83 08 999 U (EUROPEAN MIG WELDERS A/S) 24 November 1983 (1983-11-24) * page 3, line 1 - line 31; figure 1 *	1-10	B23K9/32 B23K9/173
A	US 5 472 024 A (ROBIN ALAIN ET AL) 5 December 1995 (1995-12-05)		
			TECHNICAL FIELDS SEARCHED (InCL.7)
			B23K
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 11 October 2004	Examiner Caubet, J-S
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03.82 (p04001)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 04 01 2055

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

11-10-2004

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 8308999	U	24-11-1983	DE 8308999 U1	24-11-1983
US 5472024	A	05-12-1995	FR 2689209 A1	01-10-1993
			AR 248308 A1	12-07-1995
			AT 139320 T	15-06-1996
			AU 657410 B2	09-03-1995
			AU 3893093 A	08-11-1993
			BR 9305456 A	27-09-1994
			CA 2110274 A1	14-10-1993
			CN 1079928 A	29-12-1993
			DE 69303135 D1	18-07-1996
			DE 69303135 T2	10-10-1996
			DK 589015 T3	01-07-1996
			EP 0589015 A1	30-03-1994
			ES 2089812 T3	01-10-1996
			FI 935294 A	24-01-1994
			WO 9320383 A1	14-10-1993
			GR 3020630 T3	31-10-1996
			JP 6508198 T	14-09-1994
			ZA 9302325 A	20-12-1993